


# gravity-s



## INTERNAL SHOCK ABSORBER



|   |
|---|
| HS CODE   |
| 63079098  |
| CARTON SIZE / PCS.  |
| 80 x 40 x 24 cm / 10  |
| AET (EU) N°2777/10960-04/E01-01   |
| <b>Satra Technology Europe Ltd., N° 2777,</b><br>Bracetown Business Park, Clonee,<br>Dublin, D15YN2P, Ireland               |
| MODULE D FI14/14003.01  |
| <b>SGS Fimko Oy, N°0598</b><br>Takomotie 8,<br>00380 HELSINKI, Finland  |
| AET (UKCA) N°AB0321/16077-01/E01-01   |
| <b>Satra Technology Centre, N°0321</b><br>Wyndham Way, Telford Way, Kettering<br>Northamptonshire, NN16 8SD, United Kingdom |
| MODULE D 11 IN14/14003  |
| <b>SGS United Kingdom Ltd., N°0120</b><br>Unit 202B, Worle Parkway,<br>Weston-super-Mare, BS22 6WA, United Kingdom          |

|                        |                                      |
|------------------------|--------------------------------------|
| REF.                   | FA 30 1000 20                        |
| LG.<br>(MIN./MAX.)<br> | 1.4 m / 2.0 m (connectors included)  |
| KG                     | 140 KG                               |
| CE                     | EN 355:2002                          |
| MAT.                   | 45 mm<br>PES                         |
|                        | INTERNAL SHOCK ABSORBER              |
|                        | <br>QUARTER / DOUBLE ACTION          |
|                        | YES                                  |
| +                      | PPE-R 11.063<br>X1<br>FALL INDICATOR |
|                        | 1.88 KG                              |



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitore di energia  
**Breite des Falldämpfers**

LG.  
(MIN./MAX.)



**Longueur (mini/maxi) Poids maxi utilisateur**  
**Length (min./max.) Max. user weight**  
**Longitud (mínima/máxima) Peso máximo del usuario**  
**Lunghezza (mini/maxi) Peso Max. dell'utente**  
**Länge (min./max.) Höchstgewicht des Benutzers**



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**