

NEWTON 4 HL 10 103 00


HS Code : 85131000
Barcode : 3700671407814



600
Lumens



175g
Weight



80m
Range



IP65
Rating



Li-Ion
Battery
(3,7V /
2600 mAh)
(supplied)



2m
Shock
Resistant



USB Type-C
Charger
(supplied)

	Brightness	Running Time
Focused 100%	450 lumens	5 hours 30 mins
Focused + Flood 100%	600 lumens	4 hours
Flood 100%	300 lumens	5 hours
Flood 50%	150 lumens	11 hours 30 mins
Flood 5%	20 lumens	30 hours

Charging time : 4,5 h

Charging indicator : Green blink - charging
Green - full

Dimensions

68 x 40 x 30 mm. / printed box : 171 x 109 x 50 mm

Safety

Directive **2014/30/UE**
2001/95/UE
2011/65/UE
2012/19/UE



LED Risk(c) : Group 1 - Risk limited by normal behavioural limitations. Measures under NF EN 62471 Standard.

Assets

- Powerful (600 lumens).
- Cree XP-G LED Ra > 90.
- Double light beams.
- IP65 : excellent water and dust resistance.
- Easy to use : only one button.
- Supplied with a set of 4 helmet clips.
- Removable top strap.

Use

- **Flood** for working near feet area; Flood **Ra>90 - 4500°k** for night vision or close-in work application & eye comfort; **Focused** for work within easy reach.
- **Indication of remaining capacity in the battery** <10% the light will blink 3 times.
- **Temperatures:** -10°C / +40°C.
- **Application:** Industry, Construction, Maintenance, roadworks, Networks & work at height.



Eco body under directive 2012/19/EU (D3E):
ECOLOGIC
Unique identifier: A6340
Eco body under directive 2006/66/EC: CORE-
PILE
Unique identifier: FR300504_06XKUX